IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:
ROSENBERG et al.

Application No.: 10/005,924

Group Art Unit: 2874

Filed: December 4, 2001

Examiner: Not yet assigned

For: *Circuit Interconnect for Optoelectric Device for Controlled Impedance at High Frequencies*

Attorney Docket No.: 9775-0048-999

FEE TRANSMITTAL SHEET

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

The fee required to be filed with the accompanying amendment of even date herewith concerning the above-identified application has been estimated to be $246.

The claim amendment fee has been estimated as shown below:

	(Col. 1)		(Col. 2)		(Col. 3)	SMALL ENTITY			OTHER THAN A SMALL ENTITY		
	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NO PREVIOUSLY PAID FOR		PRESENT EXTRA	RATE	ADDIT. FEE	OR	RATE		ADDIT. FEE
TOTAL	45	MINUS	36	=	9	× 9	$		× 18	$	162.00
INDEP.	5	MINUS	4	=	1	× 42	$		× 84	$	84.00
☐ FIRST PRESENTATION OF MULTIPLE DEP. CLAIM						140	$		280	$	
						TOTAL	$	OR	TOTAL	$	246.00

Please charge the required fee to Pennie & Edmonds LLP Deposit Account No. 16-1150. A copy of this sheet is enclosed.

Respectfully submitted,

Date January 25, 2002

31,066
Gary S. Williams (Reg. No.)

PENNIE & EDMONDS LLP
3300 Hillview Avenue
Palo Alto, CA. 94304
(650) 493-4935

Express Mail No. EL 452 482 131 US

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application of: Rosenberg et al.

Application No.: 10/005,924 Group Art Unit: 2874

Filed: December 4, 2001 Examiner: To be assigned

For: Circuit Interconnect for Optoelectric Device for Controlled Impedance at High Frequencies

Attorney Docket No.: 9775-0048-999

January 25, 2002

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

IN THE CLAIMS

Add the following claims:

37. An optoelectronic assembly comprising:

an optoelectronic device housed in a transistor outline package having a base and a signal lead that traverses an aperture in the base;

the optoelectronic device including

an optoelectronic component; and

a sub mount on which the optoelectronic component is mounted;

the submount incorporating at least one electrical component coupled at one end to the signal lead and coupled at another end to the optoelectronic component;

wherein the at least one electrical component forms a network that is configured so that, for operation in a predefined range of frequencies above 3 GHz, transmission